

# Towards the Measurement of Ablation Products in Hypersonic Boundary Layers



Current & Upcoming Ground Testing Efforts in Sandia's Diagnostic Sciences Department


Joshua Hargis, Kyle Daniel, Kyle Lynch, Sean Kearney, Justin Wagner  
Diagnostic Sciences Department, Sandia National Laboratories, Albuquerque, NM

12<sup>th</sup> Ablation Workshop

Lexington, Kentucky

November 9-10, 2022

# Motivation: Ablation & Gas-Surface Interactions



Hypersonic flow, high gas temperature, and elevated surface temperatures are critical to enacting the proper physical/chemical mechanisms

## Shock Layer (Gas Chemistry)


- Species dependent thermodynamic nonequilibrium
  - Vibrational temp  $\neq$  rotational temp ( $T_v \neq T_R$ )
- Dissociation produces atomic N and O and formation of nitric oxide (NO)

## Surface Chemistry

- N and O interact (adsorb) with surface.
- Oxidation and nitridation
- CN, CO, CO<sub>2</sub> production.

## Boundary Layer


- Diffusion of oxidization products
- Air chemistry
- Vibrationally excited species (N<sub>2</sub>, O<sub>2</sub>)



How can we replicate these physics in a ground test facility?

# Air-Carbon Ablation Model Considerations

- Various literature models available
  - Park, et al. (1976)
  - MURI (2015)
  - Prata (2022)
- Differences in model formulation
  - Number of reactions
  - Active surface site treatment
  - Model formulation data
- Model Comparisons (US3D)
  - Which is correct?
- Need speciation data for validation



Thanks to Erin Mussoni (SNL) for performing these simulations

# Established Methods for TPS Characterization


Solar Tower & Solar Furnace (SNL)



Arc-Jet (e.g. AEDC)



Laser Heating (e.g. LHMEI)



Plasma Torch (e.g. UT-Austin)




## Summary

- Each method produces the realistic heating over run times of several minutes.
- These facilities cannot reproduce flight velocity, aerodynamic heating and the correct air chemistry concurrently.

We desire to conduct experiments and observe ablation products in a coupled aero-thermal environment



# A Compliment to Traditional Material Characterization Facilities: Sandia Hypersonic Shock Tunnel (HST)



## Tunnel Specifications


- Nozzle Exit Dia. = 0.36 m
- Test section diameter 0.5 m
- Run times of 1-2 milliseconds

$U_{\infty}$ (m/s)	$H_0$ (MJ/kg)	$T_0$ (K)	$P_0$ (MPa)
2850	4.6	3400	12
4060	9	6000	17

Target applications include high-temperature surface chemistry and hypersonic thermochemistry.



# Survey of Upcoming Experiments in HST

- HST introduces flow complexities
  - Stagnation region gases react
  - Gas rapidly expanded through nozzle
  - Result: thermal non-eq., N-O added
- Free-stream characterization necessary
  - Temperature: CARS for heteronuclear molecules
  - Velocity: NO LIF
- Examine boundary layer products
  - Speciation/temperature of CO
    - Laser absorption
    - CARS (Coherent Anti-Raman Stokes



# Free-Stream Characterization: Temperature




- Free-stream conditions
  - Major source of uncertainty in shock tunnels
  - Temperature non-eq. in nozzle is expected
- Simulation of nozzle temperatures
  - Significant  $T_v$  differences between species
  - $N_2$  has highest degree of non-eq
- Characterizing temperature non-eq. in HST
  - Use CARS to measure  $T_{vib}$ ,  $T_{rot}$  for  $N_2$
  - Further improvement needed for  $T_{rot}$
  - Next:  $O_2$  CARS temp. measurements



# Free-Stream Characterization: Velocity

- NO is present in shock tunnel flow ( $X_{\text{NO}} \sim 4\text{-}5\%$ )
- Tracer for flow visualization
- Nitric Oxide Tagging Velocimetry
- Long fluorescence lifetime,  $>100\text{ ns}$ 
  - $U_{\infty} = 3\text{ km/s} = 3\text{ }\mu\text{m/ns}$ ,  $\Delta t \sim 100\text{ ns} \rightarrow \Delta x \sim 300\text{ }\mu\text{m}$
  - Track NO fluorescence at high image magnification

LIF beam tracks flow






# Impulse Facility Material Testing Considerations

- Generate free-stream condition in HST

- How to achieve realistic  $T_w$ ?



- Impulse facilities
  - Short test time
  - Unable to achieve realistic  $T_w$
  - Must preheat model

- Resistively heat models

- Joule heating:  $T \propto I_{supply}^2 R_{Mat'l}$
- *Hot Wall Re-entry Testing in Hypersonic Facilities*, Zander et al. 2013 (others)

- Graphite Coupons


- Good surrogate for wall mat'l.
- Easily scalable





# Tunnel Experiments: Mounting and Pyrometer

- Model Mounting Within HST

- High-temperature 3D printed plastic
  - Electrical isolation of electrodes



- Mirror mounted within test section to provide better viewing angle of model front surface




Heating process prior to an experiment

- Pyrometer (Prior to Experiment)

Lower Temp  $\sim 800$ - $1000$  K, no filters




Higher temp w/filters:  $\sim 2550$  C  $\approx 2825$  K








# Extension to Larger Test Model Geometry

- Original TPS Geometry Was Proof-of-Concept
  - Subject to 3D flow effects
  - Insufficient probe volume for diagnostics
- Modify TPS Geometry to Simulate 2D Flow
  - Utilize same cylindrical cross-section
  - Elongate span from 10 mm to 100 mm
- Measure boundary layer products (CO, etc)
  - Laser absorption spectroscopy
  - CARS (for temperature, concentrations)



# Complimentary Measurements in UT ICP

- Collaboration with UT
  - Used CARS to measure
    - $N_2$  temperatures
    - $CO/N_2$  mass ratios
  - Utility
    - High resolution
    - Near-surface detection
  - Challenges:
    - High luminosity/temp
- Next: Measurements in SNL HST
  - Pulseburst CARS in TPS boundary layer
- Compare HST/ICP CARS data w/models





# Conclusions

- Ablation modeling
  - Predictions vary between models
  - Validation needed
  - Sparse literature data
- Utilize HST in TPS characterization
  - Replicate hypersonic flow
  - Thermo-chemical
  - Velocity
- Free-stream characterization needed
  - $N_2$  CARS,  $T_{\text{rot, vib}}$
  - NO PLIF,  $U_\infty$
- Impulse facility test times
  - Model preheating required
  - Use pyrometer to measure  $T_w$
- Stay Tuned: Boundary Layer Data
  - Laser Absorption measurements (CO)
  - CARS measurements of temp., relative concentrations
  - More UT Plasma torch measurements

# Questions?